

CDC-110 Classroom Intruder Cylindrical



Performance Feature:

- **ANSI:** ANSI/BHMA A156.2–2011 Grade 1 Certified.
- **UL:** 3 hours fire rating certified
- **Door Thickness:** 1-3/8"-2" (35mm-51mm)
- **Backset:** 2-3/4" (70mm, standard), 2-3/8" (60mm), 3-3/4" (95mm), 5.0" (127mm)
- **Latch:** Stainless steel powder metal latch bolt with 1/2" (12.7mm) throw. Anti-friction fire door latch with 3/4" (19mm) throw also available.
- **Rose:** Steel or brass, 3-1/2" in diameter. Engraved arrow to indicate lock direction.
- **Lever:** Zinc Alloy, Sentinel or Quest
- **Cylinder:**
 - 6 pin solid brass cylinder Schlage C Keyway standard.
 - Small Format IC Core Cylinder also available.
 - High Security KIL Cylinder available
 - Schalge LFIC less core available
- **Available Finish:** US26D and US10B

Code Compliance:

- ANSI/BHMA A156.2-2011 Grade 1 Certified
- UL: Listed 3-hour fire rating
- BAA: Meets guidelines of The Buy American Act
- ADA: Meets requirements of The Americans with Disabilities Act



TownSteel Inc. 17901 Railroad Street, City of Industry, CA 91748

Toll Free: 877-858-0888 Tel: 626-965-8917 Fax: 626-965-8919 <http://www.townsteel.com>