


DBT Series

Deadbolt Locks



www.townsteel.com



DBT-61



DBT-61 (SFIC)



DBT-50 (Thumb Turn)



DBT-70 (Indicator outside)

Specifications

- Door Thickness** 1-3/8" - 1-3/4", 2" optional
- Backset** DBT-50 with 2-3/4" standard, 2-3/8" optional, all others with the 2-3/4" - 2-3/8" adjustable backset.
- Strike** Rectangular with door reinforce 1-1/8" x 2-3/4" square corner standard
- Deadbolt** Solid brass with hardened steel rod insert, full 1" throw
- Faceplate** 1-1/8" x 2-1/4", square corner standard, 1" x 2-1/4" optional
- Finish** 622, 626 or special finishes upon request
- Cylinder** 6 pin solid brass Schlage "C" keyway standard, SFIC with or without core optional

Code Compliance

ANSI/BHMA: Meets Industry Standards

UL: UL 3 hour listed

Warranty

Limited 5 Year Warranty

How To Order

Series	DBT DeadBolt Lock		<p>Series Finish Cylinder</p> <p>DBT - 50 - 626 - 2-3/4 - IC</p> <p>Function Backset</p>
Function	50: Thumb Turn Only 62: Double cylinder 70: Thumb Turn with Indicator	61: Single cylinder, w/Thumb Turn 65: Classroom 81: Cylinder with blank plate	
Finish	622/US19 Flat Black 626/US26D Satin Chrome Special Finishes Upon Request		
Backset	2-3/4", 2-3/8" optional (DBT-50) 2-3/4 -2/3/8" adjustable (all others)		
Cylinder	Standard: - Schlage C keyway 6 pin Optional: - IC: SFIC less core 6 or 7 pin Others available upon request		