




ED6700 SERIES

NARROW STILE EXIT DEVICES

ED6700—Grade 1 Concealed Vertical Rod Narrow Stile Exit Device



Specifications

- For Doors** Metal or Aluminum Glass doors with 1-3/4" minimum stile width
- Door Thickness** 1-3/4", single or double door application
- Chassis** Non-ferrous alloy
- Cover** Brass, Bronze or Stainless Steel
- Mounting** Furnished with wood and machine screws
- End Cap** Brass, Bronze or Stainless Steel
- Rail Assembly** Heavy gauge brass, bronze or stainless steel
- Spring** Stainless steel
- Top Bolt** Stainless steel, 7/16" travel projection, adjustable to 1"
- Bottom Bolt** Stainless steel, 7/16" travel projection, adjustable to 1"
- Top Strike** 260 type
- Bottom Strike** 265 type
- Dogging** Allen wrench type
- Finish** US10B and US32D

Dimensions

Push rail height to finished floor	41" at center
Push rail projection	Neutral 2-1/2", Depressed 1-7/8"
Center case	8-1/16" x 1-1/8" x 2"

Model	Actual Length	Max Cut Down	Door Size
ED6700-3684	34-1/2"	8"	28" to 36" wide, 84" high
ED6700-4896	46-11/32"	13-25/32"	37" to 48" wide, 96" high

Options

- Alarm kit** Available. Indicate ALRM on part number
- Mullion** Available upon request

Code Compliance

- UL/ULC** Listed Panic and Safety for all types of 4'x8' single and 8'x8' double doors
- ANSI/BHMA** Meet A156.3 Grade 1 Requirements
- BAA** Meet requirements of the Buy American Act