

XMRXA 2000 Specifications



Electronic Specifications

Electronic lock	Stand alone electronic lock, programmable at the lock
Keypad	12 key illuminated metal button keypad
PIN	4-6 digit PIN
Capacity	100 PIN code capacity
Memory	Non-volatile memory
Battery	Battery operated, low battery warning
Weather	Weather resistant
Warranty	2 year limited for electronic

Mechanical Specifications

Application	For facilities housing patients at risk
Door Thickness	1-3/4"
Backset	2-3/4"
Handing	Handed
Latch Bolt	Stainless steel, deadlocking, 1/2" throw
Faceplate	1-1/8" x 2-1/4"
Strike	ASA strike standard, 1-1/4" x 4-7/8"
Escutcheon	Steel or zinc alloy
Lever	Zinc or stainless steel
Finish	630 (US32D) finish
Cylinder Specification	6 pin Schlage® C keyway, standard Small Format IC (SFIC) with or without core Best IC core, 6 or 7 pin core, Best® "A" keyway Corbin, Schlage, Yale, Sargent Large Format 1.C. available less core High Security Cylinder available, 6 pin, TownSteel "L" keyway High Security SFIC Core available, 7 pin, TownSteel "L" keyway
Warranty	10 year limited for mechanical

Code Compliance

ANSI/BHMA	A156.13 Grade 1 Certified
UL/ULC	UL 1 QC Listed 3 Hour Fire Rating
BAA	Meets requirements of the Buy American Act
ADA	Meets requirements of the Americans with Disabilities Act