

LID Series

Deadlatch Locks



Features

- Mechanical deadlock for residential security
- Deadlatch locks automatically when door closed
- Combine the security and functionality benefits of a deadlock
- Optional double cylinder deadlatch – operated by Key from either side of the door

Specifications

- Door Thickness: 1-3/4" standard
- Backset: 2-3/4"-2-3/8" adjustable standard
- Strike: Full lip, round corner standard. Others upon request
- Faceplate: 1" x 2-1/4" round corner standard.
1-1/8" x 2-1/4" square corner optional
- Cylinder: Schlage C keyway 6 pin standard. Others upon request
- Finish: 622, 626 or others upon request

Code Compliance

- **ANSI/BHMA:** Meets ANSI/BHMA A156.36 Grade 1
- **UL:** UL 3 hour listed 

Warranty

Limited 10 Year Warranty

How To Order

Series	LID-AS1000
Function	S: Single cylinder, w/Thumb turn D: Double cylinder C: Concealed w/Thumb turn only
Finish	622: US19, Flat Black 626: US26D, Satin Chrome Others upon request
Cylinder	Standard: - SC (KIK): Schlage "C" keyway, 6 pin Optional: - SFIC/LFIC: Small or Large format IC with or without core, 6 or 7 pin - HS: High Security TownSteel L keyway, 6 or 7 pin

