

ED-MRX-A

Rim Exit Device with Ligature Resistant Trim- Arch



Ligature Resistant Trim Specifications

- For facilities housing patients at risk
- For 1-3/4" door thickness, other upon request
- 2-3/4" backset
- Handed
- 630 (US32D) finish
- Stainless steel under plate, 7-1/2" x 2-3/4" x 1/2"
- 5-point ligature resistant stainless steel arch lever
- Stainless steel turn piece, ligature resistant, ADA
- Stainless steel faceplate, 1-1/4" x 8"
- Stainless steel strike, ASA, 1-1/4" x 4-7/8"
- Through-bolt mounting, tamper resistant mounting screws, for wood and metal door
- 10-year limited warranty

Rim Exit Device Specifications

- Strikes: 900 Rigid Strike standard
- Alarm: Available with AK9
- Latch bolt: Stainless Steel, 3/4" (19mm) throw
- Dead Latch bolt: Stainless Steel
- Dogging Feature: 1/2 turn hex dogging standard for non-fire rated devices
- Cylinder Dogging: Available with CD9
- Door Size: 36" (914mm) standard, 48" (1219mm) available
- Minimum Stile Width: 4 3/4" (120mm)
- 10-year limited warranty

Code Compliance

ANSI/BHMA: A156.13 Grade 1 Certified
 UL/ULC: UL 10C Listed 3 Hour Fire Rating
 BAA: Meets requirements of the Buy American Act
 ADA: Meets requirements of the Americans with Disabilities Act



How To Order

Trim	ED-MRX-A-Rim Exit Device with Ligature Resistant Arch Trim
Function	F01 (Passage), F41 (Dummy)
Handing	LHR / RHR

Function

ED-MRX-A - 01 - LHR

Trim Handing