






















Functions

Ligature Resistant Electrified Mortise Series

Outside	Inside	Series/ Function	Type	ANSI No.	Function Description
		XMRXA-121 XMRXK-121 XMRXL-121	12VDC Fail Safe, 3-position monitoring	N/A	12VDC voltage, fail safe, Monitors Request-to-Exit, Door Position Status and Latch Position Status. Latch bolt is operated by lever from either side when no power is supplied. Powering unit locks outside lever. When locked, latch bolt can be retracted by key or lever on inside. Auxiliary latch bolt.
		XMRXA-122 XMRXK-122 XMRXL-122	12VDC Fail Secure 3-position monitoring	N/A	12VDC voltage, fail secure, Monitors Request-to-Exit, Door Position Status and Latch Position Status. Powered unit latch bolt is operated by lever from either side. When no power is applied outside lever is locked. When locked, latch bolt can be retracted by key or lever on inside. Auxiliary latch bolt.
		XMRXA-121C XMRXK-121C XMRXL-121C	12VDC Fail Safe RQE	N/A	12VDC, fail safe. Monitors Request-to-Exit (RQE). Latch bolt is operated by lever from either side when no power is applied. When power is applied levers are inoperative (locked) on both sides. When locked the latch bolt can be retracted by key on either side. Auxiliary latch bolt.
		XMRXA-122C XMRXK-122C XMRXL-122C	12VDC Fail Secure RQE	N/A	12VDC, fail secure. Monitors Request-to-Exit (RQE). Powered unit is unlocked and latch bolt is operated by lever on either side. When no power is applied levers are inoperative (locked) on both sides. When locked, the latch bolt can be retracted by key on either side. Auxiliary latch bolt.
		XMRXA-121DB XMRXK-121DB XMRXL-121DB	12VDC Fail Safe, Dead Bolt RQE	N/A	12VDC voltage, fail safe, with dead bolt, Monitors Request-to-Exit. Latch bolt is operated by lever from either side when no power is supplied. Powering unit locks both lever. Dead bolt can be operated from outside with key and inside by thumb turn. When locked, latch bolt can be retracted by key or lever on inside. Rotating inside lever retracts both bolts. Auxiliary latch bolt.
		XMRXA-122DB XMRXK-122DB XMRXL-122DB	12VDC Fail Secure Dead Bolt RQE	N/A	12VDC voltage, fail secure, with dead bolt, Monitors Request-to-Exit. Powered unit latch bolt is operated by lever from either side. When no power is applied outside lever is locked. Dead bolt can be operated from outside with key and inside by thumb turn. When locked, latch bolt can be retracted by key or lever on inside. Rotating inside lever retracts both bolts. Auxiliary latch bolt.
		XMRXA-121DC XMRXK-121DC XMRXL-121DC	12VDC Fail Safe, Dead Bolt RQE	N/A	12VDC, fail safe with dead bolt, Monitors Request-to-Exit (RQE). Latch bolt is operated by lever from either side when no power is applied. When power is applied levers are inoperative (locked) on both sides. When locked, the latch bolt can be retracted by key on either side. Dead bolt can be operated on both sides by key. When unlocked, operating inside or outside lever retracts both bolts. Auxiliary latch bolt.













Functions

Ligature Resistant Electrified Mortise Series

Outside	Inside	Series/ Function	Type	ANSI No.	Function Description
		XMRXA-122DC XMRXK-122DC XMRXL-122DC	12VDC Fail Secure Dead Bolt RQE	N/A	12VDC, fail secure with dead bolt. Monitors Request-to-Exit (RQE). Powered unit is unlocked and latch bolt is operated by lever on either side. When no power is applied levers are inoperative (locked) on both sides. When locked, the latch bolt can be retracted by key on either side. Dead bolt can be operated on both sides by key. When unlocked, operating inside or outside lever retracts both bolts. Auxiliary latch bolt.
		XMRXA-121RQE XMRXK-121RQE XMRXL-121RQE	12VDC Fail Safe RQE	N/A	12VDC voltage, fail safe, Monitors Request-to-Exit. Latch bolt is operated by lever from either side when no power is supplied. Powering unit locks outside lever. When locked, latch bolt can be retracted by key from outside or lever on inside. Auxiliary latch bolt.
		XMRXA-122RQE XMRXK-122RQE XMRXL-122RQE	12VDC Fail Secure RQE	N/A	12VDC voltage, fail Secure, Monitors Request-to-Exit. Powered unit latch bolt is operated by lever from either side. When no power is supplied, outside lever is locked. When locked, latch bolt can be retracted by key from outside or lever on inside. Auxiliary latch bolt.
		XMRXA-241 XMRXK-241 XMRXL-241	24VDC Fail Safe 3-position monitoring	N/A	24VDC, fail safe, Monitors Request-to-Exit, Door Position Status and Latch Position Status. Latch bolt is operated by lever from either side when no power is supplied. Powering unit locks outside levers. When locked, the latch bolt can be retracted by key or lever on inside. Auxiliary latch bolt.
		XMRXA-242 XMRXK-242 XMRXL-242	24VDC Fail Secure 3-position monitoring	N/A	24VDC, fail secure, Monitors Request-to-Exit, Door Position Status and Latch Position Status. Powered unit latch bolt is operated by lever from either side. When no power is applied outside lever is locked. When locked, latch bolt can be retracted by key or lever on inside. Auxiliary latch bolt.
		XMRXA-241C XMRXK-241C XMRXL-241C	24VDC Fail Safe RQE	N/A	24VDC, fail safe. Monitors Request-to-Exit (RQE). Latch bolt is operated by lever from either side when no power is applied. When power is applied levers are inoperative (locked) on both sides. When locked the latch bolt can be retracted by key on either side. Auxiliary latch bolt.
		XMRXA-242C XMRXK-242C XMRXL-242C	24VDC Fail Secure RQE	N/A	24VDC, fail secure. Monitors Request-to-Exit (RQE). Powered unit is unlocked and latch bolt is operated by lever on either side. When no power is applied levers are inoperative (locked) on both sides. When locked, the latch bolt can be retracted by key on either side. Auxiliary latch bolt.

Functions

Ligature Resistant Electrified Mortise Series

Outside	Inside	Series/ Function	Type	ANSI No.	Function Description
		XMRXA-241DB XMRXK-241DB XMRXL-241DB	24VDC Fail Safe Dead Bolt RQE	N/A	24VDC voltage, fail safe, with dead bolt, Monitors Request-to-Exit. Latch bolt is operated by lever from either side when no power is supplied. Powering unit locks outside lever. Dead bolt can be operated from outside with key and inside by thumb turn. When locked, latch bolt can be retracted by key or lever on inside. Rotating inside lever retracts both bolts. Auxiliary latch bolt.
		XMRXA-242DB XMRXK-242DB XMRXL-242DB	24VDC Fail Secure Dead Bolt RQE	N/A	24VDC voltage, fail secure, with dead bolt, Monitors Request-to-Exit. Powered unit latch bolt is operated by lever from either side. When no power is applied outside lever is locked. Dead bolt can be operated from outside with key and inside by thumb turn. When locked, latch bolt can be retracted by key or lever on inside. Rotating inside lever retracts both bolts. Auxiliary latch bolt.
		XMRXA-241DC XMRXK-241DC XMRXL-241DC	24VDC Fail Safe Dead Bolt RQE	N/A	24VDC, fail safe with dead bolt. Monitors Request-to-Exit (RQE). Latch bolt is operated by lever from either side when no power is applied. When power is applied levers are inoperative (locked) on both sides. When locked, the latch bolt can be retracted by key on either side. Dead bolt can be operated on both sides by key. When unlocked, operating inside or outside lever retracts both bolts. Auxiliary latch bolt.
		XMRXA-242DC XMRXK-242DC XMRXL-242DC	24VDC Fail Secure Dead Bolt RQE	N/A	24VDC, fail secure with dead bolt. Monitors Request-to-Exit (RQE). Powered unit is unlocked and latch bolt is operated by lever on either side. When no power is applied levers are inoperative (locked) on both sides. When locked, the latch bolt can be retracted by key on either side. Dead bolt can be operated on both sides by key. When unlocked, operating inside or outside lever retracts both bolts. Auxiliary latch bolt.
		XMRXA-241RQE XMRXK-241RQE XMRXL-241RQE	24VDC Fail Safe RQE	N/A	24VDC voltage, fail safe, Monitors Request-to-Exit. Latch bolt is operated by lever from either side when no power is supplied. Powering unit locks outside lever. When locked, latch bolt can be retracted by key from outside or lever on inside. Auxiliary latch bolt.
		XMRXA-242RQE XMRXK-242RQE XMRXL-242RQE	24VDC Fail Secure RQE	N/A	24VDC voltage, fail secure, Monitors Request-to-Exit. Powered unit latch bolt is operated by lever from either side. When no power is applied, outside lever is locked. When locked, latch bolt can be retracted by key from outside or lever on inside. Auxiliary latch bolt.