

# XMRX-K / XMRX-K-303



## Electrified/Motorized Mortise Lock with Ligature Resistant Trim-Knob



Escutcheon  
(XMRX-E-K)



Sectional  
(XMRX-S-K)



PCU (required for motorized units only)



### Mechanical Specifications

- For facilities housing patients at risk
- ANSI Grade 1 heavy duty mortise lock with ligature resistant safety knob trim
- Escutcheon (XMRX-E-K) or sectional (XMRX-S-K) trim set
- Backset 2-3/4"
- Door thickness: 1-3/4" standard, other upon request
- Stainless steel knob trim
- Stainless steel latch bolt, split, anti-friction, 3/4" throw
- Stainless steel dead bolt, with anti-saw pins, 1" projection
- Stainless steel thumb turn
- Stainless steel ANSI strike
- Tamper resistant stainless steel mounting screws
- Handing field reversible
- Schlage "C" keyway, brass 6 pin cylinder standard
- SFIC with or less core available, 6 or 7 pin core
- Schlage® LFIC less core available
- Corbin® LFIC less core available
- High security cylinder available, TownSteel "L" keyway, 6 pin
- High security SFIC core available, TownSteel "L" keyway, 7 pin
- Keyed Different standard, KA, MK, GMK, GGMK and construction keying available
- 630 (US32D) finish
- Warranty: 2-year limited warranty

### Electronic Specifications

- Solenoid units 12 or 24 VDC installations, Motorized units 12 to 24 VDC
- All motorized units are field adjustable for Fail Safe or Fail Secure
- Optional status sensors for Solenoid units: RQE, DP, LP
- Optional status sensors for motorized units: RQE, PRIV, DAJ, MKO
- Power Conversion Unit (PCU) converts 12-24VDC to operating voltage

### Code Compliance

- ANSI/BHMA: A156.13 Grade 1 Certified
- UL/ULC: UL 10C Listed 3 Hour Fire Rating
- BAA: Meets requirements of the Buy American Act



### Important Note

It is TownSteel's position that if any of our keyed locks are to be used less cylinder, whether I.C. or standard, and another manufacturer's cylinder is to be used in place of the TownSteel original manufacturer's cylinder, that a sample of that product be provided to TownSteel in advance for testing.

How To Order		Function	Handing
Trim	XMRX-E-K Electrified Ligature Resistant Mortise-Escutcheon Trim with Knob XMRX-S-K Electrified Ligature Resistant Mortise-Sectional Trim with Knob	<b>XMRX-E-K - 121 - SC - LH</b>	
Function	Please Refer to Electrified Function Sheet, or 303		
Cylinder	SC / SFIC6 / SFIC7 / CLFIC6 / SLFIC / L6 / L7		
Handing	LH / RH / LHR / RHR		
		Trim	Cylinder