

# XMRXL 2000, 4000, 5000BLE/RF, 6000



## ANSI Grade 1 Electronic Ligature Resistant Mortise Lock



Sectional

Escutcheon

### Mechanical Specifications

- For facilities housing patients at risk
- Door Thickness: 1-3/4"
- Backset: 2-3/4"
- Handed
- Latch Bolt: stainless steel, deadlocking, 1/2" throw
- Faceplate: 1-1/4" x 8"
- Strike: ASA strike standard, 1-1/4" x 4-7/8"
- Escutcheon: Stainless Steel
- Lever: Stainless Steel
- 6 pin Schlage® C keyway, standard
- Small format IC (SFIC) with or without core
- Best IC core, 6 or 7 pin core, Best® "A" keyway
- Corbin, Schlage, Yale, Sargent Large Format I.C. available less core
- High security 6 pin cylinder with TownSteel "L" keyway
- High security 7 pin SFIC core with TownSteel "L" keyway
- 630 (US32D) finish
- Warranty: 2-year limited for electronic; 10-year limited for mechanical

### Electronic Specifications

- Programmable at the lock or via TSE Home app
- 12 key illuminated touch keypad (4000/5000 series)
- 12 key illuminated metal button keypad (2000 series)
- 4-6 digit PIN (2000 series)
- 6-10 digit PIN code (4000/5000 series)
- TSE Home app for 5000 series
- 400 PIN code or RFID credential capacity (4000/5000 series)
- 100 PIN code capacity (2000 series)
- Non-volatile memory
- Battery operated
- Low battery warning
- Weather resistant

### Code Compliance

- ANSI/BHMA: A156.13 Grade 1 Certified
- UL/ULC: UL 10C Listed 3 Hour Fire Rating
- BAA: Meets requirements of the Buy American Act
- ADA: Meets requirements of The Americans with Disabilities Act



### Important Note

It is TownSteel's position that if any of our keyed locks are to be used less cylinder, whether I.C. or standard, and another manufacturer's cylinder is to be used in place of the TownSteel original manufacturer's cylinder, that a sample of that product be provided to TownSteel in advance for testing.

### How To Order

Trim	XMRX-S-L & XMRX-E-L Electronic Ligature Resistant Mortise with lever
Function	2000, 4000, 5000BLE, 5000RF, 6000
Cylinder	SC / SFIC6 / SFIC7 / CLFIC6 / SLFIC / L6 / L7
Handing	LH / RH / LHR / RHR

