

How to Order

Unless specified, 1000 Series Exit Device and Trim can be ordered as indicated below:

Device Only: Device No. - Finish; Example: ED1100 - 626(Panic Device)
 ED1200F - 630(Fire Rated Device)

Trim Only: Trim No. - Finish; Example: 308R - 626

Device and Trim: Device No. - Finish + Trim No. - Finish; Example: ED1400 - 626 + ED230M - 630

Optional Items: As sequenced below.

Device	Ordering example										
	ELR	ED 1500	LD	RBL	626	307	AAF	SMDF	+ C	308R	D
Prefix for Electric Options											
AL Alarm Exit											
DE Delayed Egress Device											
E Electric Mortise Lock											
ELR Electric Latch Retraction											
LM Latch Bolt Monitoring											
RX Request to Exit											
SS Signal Switch											
Blank For Regular (Non-electric) Device											
Device Number and Rating											
Panic ED 1100 RIM Fire ED 1100F RIM											
ED 1200 SVR ED 1200F SVR											
ED 1300 CVR ED 1300F CVR											
ED 1400 MORTISE ED 1400F MORTISE											
ED 1500 3PT ED 1500F 3PT											
Dogging (see page J-31)											
CD Cylinder Dogging LD Less Dogging											
ED Electric Dogging (ELR) Blank Flat/Hex Key Dogging											
Bottom Rod and Latch Options											
LBR Less Bottom Rod PL Pullman Latch											
RBL Round Bottom Latch											
Finish (see page J-8)											
605 (US3) 611 (US9) 613 (US10B) 626 (US26D)											
606 (US4) 612 (US10) 625 (US26) 630 (US32D)											
Device and Door Size											
36x84 3' Device for 2'4"~3'x7' (Standard) 4' Device for 2'10"~4'x7'											
36x96 3' Device for 2'4"~3'x8' 4' Device for 2'10"~4'x8'											
36x120 3' Device for 2'4"~3'x10' 4' Device for 2'10"~4'x10'											
Strike Options (see page J-24)											
A 106 RIM Strike F 224 VR Bottom Strike L 336 Mortise Strike											
B 108 RIM Strike G 225 VR Bottom Strike M 337 Mortise Open Back Strike											
C 136 RIM Pair Door Strike H 226 VR Bottom Strike N 338 Mortise Open Back Strike											
D 215 SVR Top Strike J 227/227F VR Bottom Strike											
E 216 CVR Top Strike K 306 Mortise Strike											
Handing for Double Cylinder Device (see page J-28)											
LHR Left Hand Reverse Bevel											
RHR Right Hand Reverse Bevel Blank For Regular Device											
Other Miscellaneous Door Information											
SMDF Single Hollow Metal Door and Frame PMDF Pair Hollow Metal Door and Frame											
SWDF Single Wood Door and Frame PWDF Pair Wood Door and Frame											
SWMF Single Wood Door and Hollow Metal Frame PWMF Pair Wood Door and Hollow Metal Frame											
Trim											
Trim Operation Options (see page J-20)											
Prefix C for Clutch Option Blank for Standard Operation											
Trim Options (see page 21)											
200 Series 201 , 202 , 203R , 203M , 205R , 205M , 215R , 215M											
300 Series 302 , 308R , 308M , 309R , 309M , 314R , 314M											
Lever / Grip Options (see page J-20)											
Lever D (Standard), Q, A, K Knob B (Standard), P, T											
Grip GD (Standard), GK											